

# FULL BODY HARNESS / STAINLESS STEEL

## SPECIFICATION FOR 9150018

**1. Permanent Upright Dorsal D-ring:** Stamped Stainless Steel with Splitted Polymer Sleeve which prevents the webbing from being damaged by the metallic contact of dorsal D-ring. MBS 23kN. Proof Load Tested.



**2. Adjustable Buckle:** provided with pull grip feature to enable easy pull down with thumb and easy to adjust straps for a good lift.



**3. Retrieval attachment confine space shoulder loops**

**4. Combination Buckle:** Stainless Steel, MBS 15kN



**5. Product Label:** with protection sleeve.

**6. Fall arrest & Retrieval attachment loops:** The loops at the ends are protected by an abrasion resistant covering. This prevents the webbing from being damaged by the metallic contact of the connector.

**7. Special Repellent Webbing:** It's oil, dirt and water repellent hence provides excellent resistance from build up of oil and dirt. Highly tear and cut resistant because does not allow abrasion due to collection of dust or dirt. Highly UV resistant webbing. Easy maintenance wipes clean in seconds.

<b>REF.</b>	9150018
<b>SIZES</b>	Standard = M-XL
<b>KG</b>	MAX. 140 KG (Instruction Manual - HLPN-2021-V1.2)
<b>AS/NZS</b>	AS/NZS 1891.1:2020
<b>Attachment</b>	Dorsal D-Ring (A), Lower Sternal Webbing (A) - use both loops together
	2 / 3
<b>MAT.</b>	
<b>MAT.</b>	Polyester - (Treated with Water and Oil Repellent Treatment)
	<b>Not Fitted</b> Can be bought as an add on - 915075
<b>kg</b>	1.20 KG
	YES

<b>SIZES</b>		<b>Number of adjustment buckles / Combination buckles</b>		<b>Confined Space Loops</b>	<b>MAT.</b>	<b>Material of rings / buckles</b>		<b>Suspension Trauma Straps</b>
<b>KG</b>	Size Max. user weight							